



Elevations are for illustration purpose only.

This distance can not exceed 1200mm

Maximum width of each glass panel is 890mm minus the gaps each side of the glass

\*\* 800mm Max. with no wall plate

Maximum dimension is A/2  
150 Min. 400 Max. 400 Max. 150 Min.

\*\* If the handrail is not fixed to the wall, the end panel can not exceed the following: 700mm without handrail insert or 800mm with. These distances must include the gaps between the glass.

Ensure glass is glazed in accordance with AS1288. Glass must be blocked to ensure it cannot dislodge from within the frame.

When Axiom products are concealed or in contact with screed, tile bed or another item that could cause corrosion, Axiom products must be adequately protected to prevent any corrosion.

It is the installers responsibility to ensure that any dissimilar metals are kept separated. Axiom Group recommends the use of nylon washers to keep dissimilar metals separated.

\* Read this drawing in conjunction with the relevant engineering drawings. All products must be installed as specified by the engineer.

	Style: AxiLume Frameless Balustrade	Scale as shown @ A1	Drawing n°. SD13-15	Checked by: HM	Job N°.	Proprietary and Confidential This drawing remains the sole property of Axiom Group Investments Pty Ltd. It must not be reproduced in part or in whole without consent from the Directors. Axiom reserves the right to amend drawings in the interest of continuous improvement. E & O E
	Suite: Panorama Suite	Paper Size: A1	Drawn by: C. Richardson	Revision: C	Drawing type: Suite drawing	
	Product: ASO3850 Stainless steel standoff fitting with ARN handrail on a ASSHH1 handrail bracket	Unless otherwise stated all dimensions are in MM	Date: 24 / 11 / 2015	This drawing has been produced using AutoCAD LT 2015		